


- Exterior Profile: MesaLine, VeeLine or Stucco
- Interior Profile: MesaLine
- Exterior Gauge: 26 (0.020"), 24 (0.023")
- Interior Gauge: 26 (0.020")
- Substrate: Galvalume®, G90 Galvanized (Grade 33) and Stainless Steel (Type 304)
- Exterior Finish: 1.0 mil thick Kynar 500®
- Interior Finish: Siliconized Polyester (USDA white), Plastisol available
- Coverage Width (B): 47.375-inch
- Thickness (A): 4, 5, 6, 8, 10 and 12-inch
- Exterior Texture: Embossed
- Interior Texture: Embossed
- Core: ROXUL® ConRock L structural mineral wool
- K-factor: 0.277 Btu-in/hr-ft²-F° @ 40° F mean temperature (R-3.61)
- Splines: Fiber-reinforced cement board (½" x 2-¾" x 8' long)
- Available Lengths: Minimum 8'-0" to maximum 30'-0"; over 30'-0", please inquire
- Note: All information subject to change without notice. Please reference website for most current data.



PANEL CROSS-SECTION



PANEL SIDELAP

PERFORMANCE

Panel Thickness (in.)	Fire Rating (hr.)	Weight (psf)	Thermal U-factor (BTU / hr • ft² • F°)	R-factor (hr • ft² • F° / BTU)
4	1	4.6	0.069	14.49
5	2	5.3	0.055	18.18
6	3	6.0	0.046	21.74
8	3	7.5	0.035	28.57
10	3	8.9	0.028	35.71
12	3	10.3	0.023	43.48

Panel Thickness (in.)	Uniform Load (psf)						
	5	10	15	20	25	30	40
4	22.2	15.7	12.8	11.1	9.9	8.2	6.2
5	24.8	17.5	14.2	12.4	10.6	9.1	6.8
6	27.3	19.3	15.7	13.6	12.1	10.1	7.6
8	31.5	22.3	18.2	15.8	14.0	11.6	8.7
10	35.2	24.9	20.3	17.6	15.6	13.0	9.8
12	38.6	27.3	22.3	19.3	17.1	14.2	10.7



21200 FM 362
Waller, TX 77484
844-807-7400